

IN THE CLAIMS:

This listing of claims will replace all prior versions and listings of claims in the application:

Listing of Claims:

1. Canceled.

2 (Currently Amended). A storing module for use in a communication network for buffering data, said storing module comprising: The storing module of Claim 1,
a cell buffer unit having a first queue and a plurality of second queues operably configured to
store protocol data units (PDU), wherein said first queue is further configured to receive a
PDU from said communication network;
a cell buffer status indicator operably configured to issue a first queue status signal and a second
queue status signal, wherein said first queue status signal indicates an occupancy status of
said first queue and said second queue status signal indicates an occupancy status of said
plurality of second queues;
a cell buffer controller operably configured to forward a PDU received in said first queue to one
of said plurality of second queues, wherein said plurality of second queues include at least a high
priority queue and a low priority queue and said forwarded PDU is forwarded to one of said high
priority queue and said low priority queue in accordance with an appended PDU priority
indicator, wherein said cell buffer controller is further operably configured to forward and fetch a
PDU to and from a remote memory unit comprising a dedicated queue for each of said plurality
of second queues.

3 (Original). The storing module of Claim 2 further including a queue status register having an output operably configured to indicate a mapped location of a PDU buffered in said dedicated queue.

4 (Original). The storing module of Claim 2, wherein said cell buffer controller is further operably configured to forward said PDU to one of said dedicated queues in said remote memory unit only when an associated one of said plurality of second queues is fully occupied.

5 (Previously Amended). The storing module of Claim 2, wherein said cell buffer controller is further operably configured to fetch forward said PDU to one of said dedicated queues in said remote memory unit when an associated one of said plurality of second queues is occupied and when said associated one of said plurality of second queues subsequently becomes partially occupied.

6 (Currently Amended). The storing module of Claim 1 ~~2~~, wherein said cell buffer unit comprising a dual port random access memory.

7 (Currently Amended). The storing module of Claim 1 ~~2~~, wherein a PDU comprises an asynchronous transfer mode cell.

8 (Currently Amended). The storing module of Claim 1 ~~2~~, wherein said cell buffer unit comprising a single port random access memory.

9 (Currently Amended). The storing module of Claim 1 ~~2~~, wherein high priority comprises real-time data and low priority comprises non-real-time data.

10 (Original). A buffering system for use in a communication network for buffering data, said buffering system comprising:

a cell buffer unit having a first queue and a plurality of second queues operably configured to store protocol data units (PDU), wherein said first queue is further configured to receive a PDU from said communication network;

a cell buffer status indicator operably configured to issue a first queue status signal and a second queue status signal, wherein said first queue status signal indicates an occupancy status of said first queue and said second queue status signal indicates an occupancy status of said plurality of second queues;

a cell buffer controller operably configured to forward a PDU received in said first queue to one of said plurality of second queues, wherein said plurality of second queues include at least a high priority queue and a low priority queue and said forwarded PDU is forwarded to one of said high priority queue and said low priority queue in accordance with an associated priority indicator appended to said forwarded PDU;

a remote memory device having a dedicated queue for each of said second queues, wherein said cell buffer controller is further operably configured to forward and fetch a PDU to and from said remote memory device.

11 (Original). The buffering system of Claim 10, wherein said cell buffer controller is further operably configured to forward a PDU received in said first queue to one of said dedicated queues only when an associated one of said high priority queue and said low priority queue is fully occupied.

12 (Original). The buffering system of Claim 10, wherein said cell buffer controller is further operably configured to fetch a PDU from one of said dedicated queues when an associated one of said high priority queue and low priority queue becomes partially occupied.

13 (Original). The buffering system of Claim 10, wherein said cell buffer unit comprises a dual port random access memory.

14 (Original). The buffering system of Claim 10, wherein a PDU comprises an asynchronous transfer mode data cell.

15 (Original). The buffering system of Claim 10, wherein said cell buffer unit comprises a single port random access memory.

16 (Original). The buffering system of Claim 10 further including a queue status register having an output operably configured to indicate a mapped location of a PDU buffer in one of said dedicated queues.

17. Canceled.

18 (Currently Amended). The method of Claim 17 19, further comprising fetching a PDU from said remote memory device for placement in a select one of said plurality of second queues when said select second queue becomes partially occupied.

19 (Currently Amended). A method of buffering protocol data units (PDU)s in a communication network, said method comprising: The method of Claim 17 further comprising
issuing a first queue status signal indicating a ready status to receive a PDU from said communication network;
receiving said PDU in said first queue;
issuing a second queue status signal indicating an occupancy status of a plurality of second queues;
forwarding said PDU received in said first queue to one of said plurality of second queues comprising at least a high priority queue and a low priority queue in a local memory unit in accordance with a priority indicator appended to said PDU;
forwarding said PDU to a corresponding queue in a remote memory device when a select one of said plurality of second queues in said local memory device is occupied; and
configuring said remote memory with a dedicated queue corresponding to each of said plurality of second queues in said local memory device.

20 (Currently Amended). The method of Claim 17 19 further comprising fetching a PDU from said high priority queue for transmission to a communication port associated with said communication network prior to fetching a PDU from said low priority queue for transmission to said communication port.

21 (Currently Amended). The method of Claim 17 19 further comprising mapping a memory location of a PDU buffered in said remote memory device.

22 (Currently Amended). The method of Claim 17 19, wherein said PDU is an asynchronous transfer mode data cell.